6 CHANNEL LC-MTP COMPACT MODULAR CASSETTE





| General Specifications | | | | | | |
|------------------------|--|-------|---|-------|-------|-------|
| Product Series | Compact Series | | | | | |
| Product Type | Cassette | | | | | |
| Polarity | DCS Types A, B & C IMPORTANT: DCS polarity types may be configured differently from TIA Standard configurations to achieve end-to-end connectivity for methods A,B and C. | | | | | |
| Fiber Count | 12 | | | | | |
| Front Adapter | LC Duplex | | | | | |
| Insertion Loss | 0.40dB Max (≤0.25-MTP; ≤0.15-LC) | | | | | |
| Dimensions | Height | 5.13" | Width | 1.10" | Depth | 3.50" |
| Colors | ECO/Silver | Black | k (Other colors available upon request) | | | |
| Application | | | | | | |

Cassettes are used to populate the 1U Modular Patch Panel or the 4U 12x Modular Patch Panel Enclosure. They are designed using ribbon assemblies in a fully protected enclosure. These compact cassettes can easily be swapped out when connector requirements change, leaving the existing trunk cable assemblies in place. Utilizing MTP connections reduces total cost of ownership.

TO ORDER, CONTACT YOUR SALES REP, OR CALL US DIRECTLY:

972-620-4997 | salessupport@datacentersys.com | datacentersys.com

